

Safety Data Sheet

according to UK REACH Regulation

REMAXX BEAD SEALER

Revision date: 01.09.2022

Product code: 00156-0032

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

REMAXX BEAD SEALER

Art.-No.

593 0807, 593 0814, 593 1394, 593 1395

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Sealant

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: REMA TIP TOP AG
Street: Gruber Strasse 65
Place: D-85586 Poing
Telephone: +49 (0) 8121 / 707 - 100
Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

Supplier

Company name: REMA TIP TOP AUTOMOTIVE UK LTD
Street: Westland Square, LEEDS
Place: West Yorkshire, LS11 5XS
Telephone: +44 (0)113 2770044
e-mail: info@tip-top.co.uk
Internet: www.rema-tiptop.co.uk

1.4. Emergency telephone number:

INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)
In England and Wales: NHS 111 In Scotland: NHS 24 - dial 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Flam. Liq. 2; H225
Eye Irrit. 2; H319
STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

Propan-2-ol

Signal word: Danger

Pictograms:



Hazard statements

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.



Safety Data Sheet

according to UK REACH Regulation

REMAXX BEAD SEALER

Revision date: 01.09.2022

Product code: 00156-0032

Page 2 of 11

Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P233 Keep container tightly closed.
- P261 Avoid breathing vapour.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P337+P313 If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

Vapours may form explosive mixture with air.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Preparation in ethanol and isopropanol

Hazardous components

| CAS No | Chemical name | | | Quantity |
|-----------|--|--------------|------------------|----------|
| | EC No | Index No | REACH No | |
| | GHS Classification | | | |
| 64-17-5 | Ethanol | | | < 25 % |
| | 200-578-6 | 603-002-00-5 | 01-2119457610-43 | |
| | Flam. Liq. 2, Eye Irrit. 2; H225 H319 | | | |
| 67-63-0 | Propan-2-ol | | | < 25 % |
| | 200-661-7 | 603-117-00-0 | 01-2119457558-25 | |
| | Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 | | | |
| 7632-00-0 | Sodium nitrite | | | < 1 % |
| | 231-555-9 | 007-010-00-4 | 01-2119471863-27 | |
| | Ox. Sol. 3, Acute Tox. 3, Eye Irrit. 2, Aquatic Acute 1; H272 H301 H319 H400 | | | |

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

| CAS No | EC No | Chemical name | Quantity |
|-----------|--|----------------|----------|
| | Specific Conc. Limits, M-factors and ATE | | |
| 64-17-5 | 200-578-6 | Ethanol | < 25 % |
| | Eye Irrit. 2; H319: >= 50 - 100 | | |
| 7632-00-0 | 231-555-9 | Sodium nitrite | < 1 % |
| | oral: LD50 = 180 mg/kg | | |

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

Safety Data Sheet

according to UK REACH Regulation

REMAXX BEAD SEALER

Revision date: 01.09.2022

Product code: 00156-0032

Page 3 of 11

If you feel unwell, seek medical advice.

After inhalation

Move to fresh air in case of accidental inhalation of vapours or decomposition products.
In the event of symptoms refer for medical treatment.

After contact with skin

Wash off with soap and plenty of water.
Consult a doctor if skin irritation persists.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Seek medical treatment by eye specialist.

After ingestion

Summon a doctor immediately.
Rinse out mouth and give plenty of water to drink.
Never give anything by mouth to an unconscious person.
Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

Causes serious eye damage.
May cause drowsiness or dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO₂), water-spray.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Fire may produce:
carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x)

5.3. Advice for firefighters

Use breathing apparatus with independent air supply.
Protective suit.

Additional information

Keep away from sources of ignition - No smoking.
Vapours are heavier than air and spread along ground.
The vapour/air mixture is explosive, even in empty, uncleaned receptacles.
Cool containers at risk with water spray jet.
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Ensure adequate ventilation.
Keep away sources of ignition.
Keep away noninvolved persons.

For non-emergency personnel

Do not breathe vapours.
Avoid contact with skin, eyes and clothing.

Safety Data Sheet

according to UK REACH Regulation

REMAXX BEAD SEALER

Revision date: 01.09.2022

Product code: 00156-0032

Page 4 of 11

For emergency responders

- In case of vapour formation use respirator.
- Use personal protective clothing.
- Use only explosion-proof equipment.

6.2. Environmental precautions

- Do not discharge into the drains/surface waters/ground water.

6.3. Methods and material for containment and cleaning up

For containment

- Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up

- Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).
- Shovel into suitable container for disposal.

6.4. Reference to other sections

- Observe protective instructions (see Sections 7 and 8).
- Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

- Keep a good ventilation and air-exhaust at the place of work.
- When using do not eat or drink.
- Avoid contact with skin, eyes and clothing.

Advice on protection against fire and explosion

- Keep product and empty container away from heat and sources of ignition.
- Do not smoke.
- Take precautionary measures against static discharges.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

- Keep container tightly closed in a dry, cool and well-ventilated place.
- Pay attention to anti-explosion rules.

Hints on joint storage

- Incompatible with oxidizing agents.

Further information on storage conditions

- Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

- Sealant

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

| CAS No | Substance | ppm | mg/m ³ | fibres/ml | Category | Origin |
|---------|-------------|------|-------------------|-----------|---------------|--------|
| 64-17-5 | Ethanol | 1000 | 1920 | | TWA (8 h) | WEL |
| 67-63-0 | Propan-2-ol | 400 | 999 | | TWA (8 h) | WEL |
| | | 500 | 1250 | | STEL (15 min) | WEL |

8.2. Exposure controls

Safety Data Sheet

according to UK REACH Regulation

REMAXX BEAD SEALER

Revision date: 01.09.2022

Product code: 00156-0032

Page 5 of 11

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Do not inhale vapours.

Avoid contact with eyes and skin.

Wash hands before breaks and immediately after handling the product.

When using do not eat, drink or smoke.

Remove and wash contaminated clothes before re-use.

Eye/face protection

Tightly fitting goggles (EN 166).

Eye wash bottle with pure water (EN 15154).

Hand protection

Protective gloves resistant to chemicals made off butyl, minimum coat thickness 0.7 mm, permeation resistance approx. 480 minutes, i.e. protective glove <Butoject 898> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Skin protection

Long sleeved clothing (DIN EN ISO 6530)

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|-----------------|-----------|
| Physical state: | Liquid |
| Colour: | Dark grey |
| Odour: | Alcoholic |
| pH-Value: | n.d. |

Changes in the physical state

| | |
|---|-----------------------|
| Melting point/freezing point: | < 0 °C |
| Boiling point or initial boiling point and boiling range: | > 78 °C |
| Sublimation point: | n.a. |
| Softening point: | n.d. |
| Pour point: | n.d. |
| Flash point: | 12 °C |
| Sustaining combustion: | Sustaining combustion |

Flammability

| | |
|---------------|------|
| Solid/liquid: | n.a. |
| Gas: | n.a. |

Explosive properties

The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated.

| | |
|----------------------------|----------------|
| Lower explosion limits: | 2 vol. % |
| Upper explosion limits: | n.d. |
| Auto-ignition temperature: | approx. 425 °C |

Self-ignition temperature

| | |
|--------|------|
| Solid: | n.a. |
|--------|------|



Safety Data Sheet

according to UK REACH Regulation

REMAXX BEAD SEALER

Revision date: 01.09.2022

Product code: 00156-0032

Page 6 of 11

| | |
|--|-----------------------|
| Gas: | n.a. |
| Decomposition temperature: | n.d. |
| Oxidizing properties | |
| Not oxidising. | |
| Vapour pressure: (at 20 °C) | approx. 57 hPa |
| Density (at 20 °C): | < 1 g/cm ³ |
| Bulk density: | n.a. |
| Water solubility: (at 20 °C) | Miscible |
| Solubility in other solvents | |
| n.d. | |
| Partition coefficient n-octanol/water: | n.d. |
| Viscosity / dynamic: | n.d. |
| Viscosity / kinematic: | n.d. |
| Flow time: | n.d. |
| Relative vapour density: | n.d. |
| Evaporation rate: | n.d. |
| Solvent separation test: | 0 % |
| Solvent content: | < 50 % |

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with oxidizing agents.

10.4. Conditions to avoid

Vapour/air mixtures are explosive at intensive warming.

Heating can release vapours which can be ignited.

10.5. Incompatible materials

oxidizing agents

10.6. Hazardous decomposition products

With secondary amines, formation of nitrosamines.

Fire may produce:

Carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x)

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

Based on available data, the classification criteria are not met.

No toxicological data available.



Safety Data Sheet

according to UK REACH Regulation

REMAXX BEAD SEALER

Revision date: 01.09.2022

Product code: 00156-0032

Page 7 of 11

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Propan-2-ol)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

11.2. Information on other hazards

Endocrine disrupting properties

No data available

Other information

High concentration of vapours may cause irritation to eyes and respiratory system and produce narcotic effects.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

If appropriately handled and if in accordance with the general hygienic rules, no damages to health have become known.

Effects of breathing high concentrations of vapour may include:

Headache, dizziness, weakness, unconsciousness.

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

12.2. Persistence and degradability

Propan-2-ol; Ethanol

Readily biodegradable (to OECD criteria).

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Low hazard to waters.

Further information

Do not flush into surface water or sanitary sewer system.

Ecological injuries are not known or expected under normal use.

Safety Data Sheet

according to UK REACH Regulation

REMAXX BEAD SEALER

Revision date: 01.09.2022

Product code: 00156-0032

Page 8 of 11

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Where possible recycling is preferred to disposal.

Can be disposed of as a solid waste or burned in a suitable installation subject to local regulations.

List of Wastes Code - residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land transport (ADR/RID)

| | |
|--|---|
| 14.1. UN number: | UN 1987 |
| 14.2. UN proper shipping name: | ALCOHOLS, N.O.S. (Ethanol, Propan-2-ol) |
| 14.3. Transport hazard class(es): | 3 |
| 14.4. Packing group: | II |
| Hazard label: | 3 |



| | |
|--------------------------|-------------|
| Classification code: | F1 |
| Limited quantity: | 1 L / 30 kg |
| Excepted quantity: | E2 |
| Transport category: | 2 |
| Hazard No: | 33 |
| Tunnel restriction code: | D/E |

Inland waterways transport (ADN)

| | |
|--|---|
| 14.1. UN number: | UN 1987 |
| 14.2. UN proper shipping name: | ALCOHOLS, N.O.S. (Ethanol, Propan-2-ol) |
| 14.3. Transport hazard class(es): | 3 |
| 14.4. Packing group: | II |
| Hazard label: | 3 |



| | |
|----------------------|-------------|
| Classification code: | F1 |
| Limited quantity: | 1 L / 30 kg |
| Excepted quantity: | E2 |

Marine transport (IMDG)

| | |
|-------------------------|---------|
| 14.1. UN number: | UN 1987 |
|-------------------------|---------|

Safety Data Sheet

according to UK REACH Regulation

REMAXX BEAD SEALER

Revision date: 01.09.2022

Product code: 00156-0032

Page 9 of 11

14.2. UN proper shipping name: ALCOHOLS, N.O.S. (Ethanol and isopropanol)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Marine pollutant: No
Limited quantity: 1 L / 30 kg
Excepted quantity: E2
EmS: F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1987
14.2. UN proper shipping name: ALCOHOLS, N.O.S. (Ethanol and isopropanol, solution)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Limited quantity Passenger: 1 L
Passenger LQ: Y341
Excepted quantity: E2
IATA-packing instructions - Passenger: 353
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 364
IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practices.

14.7. Maritime transport in bulk according to IMO instruments

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

2004/42/EC (VOC): < 50 %

Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.



Safety Data Sheet

according to UK REACH Regulation

REMAXX BEAD SEALER

Revision date: 01.09.2022

Product code: 00156-0032

Page 10 of 11

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,2,4,6,7,9,10,11,12,13,14.

Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

IMDG = International Maritime Code for Dangerous Goods

IATA/ICAO = International Air Transport Association / International Civil Aviation Organization

MARPOL = International Convention for the Prevention of Pollution from Ships

IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

REACH = Registration, Evaluation, Authorization and Restriction of Chemicals

CAS = Chemical Abstract Service

EN = European norm

ISO = International Organization for Standardization

DIN = Deutsche Industrie Norm

PBT = Persistent Bioaccumulative and Toxic

vPvB = Very Persistent and very Bio-accumulative

LD = Lethal dose

LC = Lethal concentration

EC = Effect concentration

IC = Median immobilisation concentration or median inhibitory concentration

Classification for mixtures and used evaluation method according to GB CLP Regulation

| Classification | Classification procedure |
|--------------------|--------------------------|
| Flam. Liq. 2; H225 | On basis of test data |
| Eye Irrit. 2; H319 | Calculation method |
| STOT SE 3; H336 | Calculation method |

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.

H272 May intensify fire; oxidiser.

H301 Toxic if swallowed.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.



Safety Data Sheet

according to UK REACH Regulation

REMAXX BEAD SEALER

Revision date: 01.09.2022

Product code: 00156-0032

Page 11 of 11

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)